

Solid SKS Tire and Wheel Assemblies

When skid steer tire performance is your priority use Rhino.



33 x 12-20

Move it fast... Move it safe... MOVE IT ON RHINO.

RHINO
RUBBER, LLC™

Solid SKS Tire and Wheel Assemblies

from Rhino Rubber, LLC™



Move it On Rhino

- Tires sold separately or as an assembly
- Demountable solid tires
- Can re-use the wheel
- ISO certified production
- VD tread pattern is standard

Tread Characteristics

- Disposal of mud & water
- Load capacity
- Traction ride

Recommended Applications

- Muddy or dirt surfaces
- Maximum machine width is needed
- Elevates the machine higher off the ground (32 x 10-20 & 33 x 12-20)



TIRE SIZE	RIM (inches)	O.D. (inches)	S.W. (inches)	WEIGHT (lbs) Tire only	WEIGHT (lbs) Tire/Wheel Assembly	CAPACITY 16MPH (lbs)
30 x 10-16	6.5	30.2	9.1	155	200	4963
33 x 12-20	8.0	32.9	11.8	200	310	8800

RHINO
RUBBER, LLC™

Easy to Find...Tough to Beat.

Warehouse: **234-678-7863**

Toll Free: **877-744-6603**

Fax: **888-480-8611**

Rhino Rubber Warehouse • 275-299 N. Arlington St. • Akron, OH 44306



Checkout our website at
www.rhinorubbertires.com
and be sure to click on the
Quick Quote button.